

KNOW HOW IN NO TIME

Caulking Your Bathroom

Tools & Materials Checklist

- | | |
|--|---|
| <input type="checkbox"/> Caulk Gun | <input type="checkbox"/> Caulk Tip |
| <input type="checkbox"/> Utility Knife | <input type="checkbox"/> Reusable Caulk Plug |
| <input type="checkbox"/> Caulk Removal Tool | <input type="checkbox"/> Mold Remover Spray |
| <input type="checkbox"/> Caulk Removal Liquid or Spray | <input type="checkbox"/> Rags |
| <input type="checkbox"/> Putty Knife or Finishing Tool | <input type="checkbox"/> Painter's Tape |
| | <input type="checkbox"/> Foam Backer Rod (Optional) |

3 Important Steps

- 1** Use caulk removal liquid and a utility knife or removal tool to make sure any old caulk is removed and surface is clean. Use a mold remover like Concrobium® to kill any mold.
- 2** Cut the nozzle of the caulk tube at a 45° degree angle for the desired bead size. The further down the nozzle the cut the larger the bead will be. *(Use a caulk tip for a perfect bead)* For gaps greater than ½ inch press foam backer into the space.
- 3** Use painters tape on tile or wall to create an even line of caulk on the tub wall. Apply an even bead of caulk into the gap. Use a putty knife or finishing tool to smooth the bead. Use a damp rag to wipe away excess caulk before it dries. Dried excess caulk will need to be cut or scraped away with a utility knife.

**For Step-by-Step How To's
Visit Tips at
GreatLakesAce.com**